SPECIFYING AUDIO OUTPUT ACCORDING TO WINDOW GRAPHICAL CHARACTERISTICS

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is related to the following co-pending applications, which are filed on even date herewith and incorporated herein by reference:

(1) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010513US1); and

(2) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010514US1);

(3) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010515US1);

(4) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010516US1);

(5) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010517US1);

(6) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010518US1);

(7) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010519US1);

(8) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010521US1);

(9) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010522US1);

(10) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010524US1); and

(11) U.S. Patent Application Serial No. ___/_____ (Attorney Docket No. AUS920010525US1).

BACKGROUND OF THE INVENTION

1.   Technical Field:

The present invention relates in general to computer systems and, in particular, to graphical user interfaces. Still more particularly, the present invention relates to adjusting audio output according to graphical characteristics of displayable objects with which sounds are associated.

2.   Description of the Related Art:

Most operating systems provide a graphical user interface (GUI) for controlling a visual computer environment that represents programs, files, and options with graphical images, such as icons, menus, and dialog boxes on the screen. Graphical items defined within the GUI work the same way for the user in most software because the GUI provides standard software routines to handle these elements and report the user's actions.

A typical graphical object defined by a GUI is a window or other defined area of a display containing distinguishable text, graphics, video, audio and other information for output. A display area may contain multiple windows associated with a single software program or multiple software programs executing concurrently.

Often when multiple graphical objects are displayed concurrently, the graphical objects will overlap. The order in which graphical objects are drawn on top of one another onscreen

to simulate depth is typically known as the z-order. Typically, those objects at the top of the z-axis obscure the view of those graphical objects drawn below.

In some operating systems, a level of transparency or translucency may be applied to graphical objects, and in particular to windows. By applying a level of translucency to upper level windows, lower level windows are rendered visible through the upper level windows.

Typically, audio output is limited to the sounds associated with the currently active window and operating system related sounds. However, only allowing audio output of the sounds associated with the active window is limiting, particularly where transparency is applied to windows.

In view of the foregoing, it would be advantageous to provide a method, system, and program for allowing audio output to include sounds associated with multiple windows. In addition, it would be advantageous to provide a method, system, and program for distinguishing sounds according to the graphical characteristics of the associated window.

SUMMARY OF THE INVENTION

In view of the foregoing, it is therefore an object of the present invention to provide an improved computer system.

It is another object of the present invention to provide an improved graphical user interface.

It is yet another object of the present invention to provide a method, system and program for adjusting audio output according to graphical characteristics of displayable objects with which sounds are associated.

According to one aspect of the present invention, a graphical characteristic of at least one displayable object within a user interface is detected. Graphical characteristics may include the position, the transparency, and resource utilization of at least one displayable object,

An audio output of a sound associated with at least one displayable object is adjusted to reflect the graphical characteristic, such that the audio output is specified according to a graphical display within the user interface. In addition, an environmental effect may be applied in adjusting the sound to reflect the graphical characteristic of the displayable object.

All objects, features, and advantages of the present invention will become apparent in the following detailed written description.

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the invention are set forth in the appended claims. The invention itself however, as well as a preferred mode of use, further objects and advantages thereof, will best be understood by reference to the following detailed description of an illustrative embodiment when read in conjunction with the accompanying drawings, wherein:

Figure 1 depicts one embodiment of a computer system with which the method, system and program of the present invention may advantageously be utilized;

Figure 2 illustrates a graphical representation of a user interface where audio output corresponds to the graphical characteristics of associated windows in accordance with the method, system, and program of the present invention;

Figure 3 depicts a graphical representation of a user interface where windows are z-ordered according to audio utilization in accordance with the method, system, and program of the present invention;

Figure 4 illustrates a block diagram of audio preferences in accordance with the method, system, and program of the present invention; and

Figure 5 depicts a high level logic flowchart of a process and program for adjusting sound output according to displayable object graphical characteristics in accordance with the method, system, and program of the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

A method, system, and program for adjusting audio output according to the graphical characteristics of associated windows within a graphical user interface are provided. For purposes of the present invention, graphical characteristics may include the position of a window, the transparency of a window, the color of a window, and other graphical distinguishments within a window.

In addition to windows, audio output may be adjusted according to the graphical characteristics of associated displayable objects. A "displayable object" may include text, icons, video, graphics, windows, or other logical graphical representations displayable within a display area. Displayable objects may be hidden or visible. Further, displayable objects may be layered in a z-order. Moreover, a displayable object may utilize a portion of a display area or may extend across the entirety of a display area. A displayable object may or may not include definable boundaries.

A z-order is the order along the z-axis in which displayable objects appear. Through a z-buffering technique, a depth is associated with each displayable object such that each object appears to be set at a particular depth in comparison with other displayable objects. There may be n-levels of layers within the z-order, where multiple displayable objects may be positioned within a particular n-level of the z-order.

The z-order may be a result of the order in which a user opens displayable objects onto the display. Alternatively, according to one advantage of the present invention, a user may

designate for the z-order to be set according to a particular
criteria.

Transparency is a graphical feature that is particularly
advantageous to the present invention when displaying multiple
displayable objects within a user interface where those
displayable objects may overlap. As will be understood by one
skilled in the art, by making a displayable object appear
transparent on a computer screen, other displayable objects
positioned below the transparent displayable object are rendered
visible through the transparent displayable object. Further, the
transparency of a displayable object may be adjusted from opaque
to totally transparent.

Typically, the transparency attribute is stored with color
values in an alpha channel. Then, when calculating the
appearance of a given pixel, the graphic processor uses the alpha
channel values to determine the pixel's color through a process
termed alpha blending. Through alpha blending, the process adds
a fraction of the color of the transparent object set by the
alpha channel value to the color of the displayable object below.
Mixing the colors together gives the appearance that the
displayable object below is seen through a layer of the
transparent displayable object. In addition to alpha blending,
additional shading may be added to create shadows and other
graphical images cue the viewer to the position of the
transparent displayable object.

In the following description, for the purposes of
explanation, numerous specific details are set forth to provide a
thorough understanding of the present invention. It will be
apparent, however, to one skilled in the art that the present
invention may be practiced without these specific details. In
other instances, well-known structures and devices are shown in

block diagram form to avoid unnecessarily obscuring the present invention.

HARDWARE OVERVIEW

The present invention may be executed in a variety of systems, including a variety of computing systems and electronic devices under a number of different operating systems. In one embodiment of the present invention, the computer system is a portable computing system such as a notebook computer, a palmtop computer, a personal digital assistant, a telephone or other electronic computing system that may also incorporate communications features that provide for telephony, enhanced telephony, messaging and information services. However, the computer system may also be, for example, a desktop computer, a network computer, a midrange computer, a server system or a mainframe computer. Therefore, in general, the present invention is preferably executed in a computer system that performs computing tasks such as manipulating data in storage that is accessible to the computer system. In addition, the computer system preferably includes at least one output device and at least one input device.

Referring now to the drawings and in particular to **Figure 1,** there is depicted one embodiment of a computer system with which the method, system and program of the present invention may advantageously be utilized. Computer system **10** comprises a bus **22** or other communication device for communicating information within computer system **10,** and at least one processing device such as processor **12,** coupled to bus **22** for processing information. Bus **22** preferably includes low-latency and high-latency paths that are connected by bridges and controlled within computer system **10** by multiple bus controllers.

Processor **12** may be a general-purpose processor such as
IBM's PowerPC™ processor that, during normal operation, processes
data under the control of operating system and application
software stored in a dynamic storage device such as random access
memory (RAM) **14** and a static storage device such as Read Only
Memory (ROM) **16.** The operating system preferably provides a
graphical user interface (GUI) to the user. In a preferred
embodiment, application software contains machine executable
instructions that when executed on processor **12** carry out the
operations depicted in the flowcharts of **FIG. 5** and others
described herein. Alternatively, the steps of the present
invention might be performed by specific hardware components that
contain hardwire logic for performing the steps, or by any
combination of programmed computer components and custom hardware
components.

The present invention may be provided as a computer program
product, included on a machine-readable medium having stored
thereon the machine executable instructions used to program
computer system **10** to perform a process according to the present
invention. The term "machine-readable medium" as used herein
includes any medium that participates in providing instructions
to processor **12** or other components of computer system **10** for
execution. Such a medium may take many forms including, but not
limited to, non-volatile media, volatile media, and transmission
media. Common forms of non-volatile media include, for example,
a floppy disk, a flexible disk, a hard disk, magnetic tape or any
other magnetic medium, a compact disc ROM (CD-ROM), a digital
video disc-ROM (DVD-ROM) or any other optical medium, punch cards
or any other physical medium with patterns of holes, a
programmable ROM (PROM), an erasable PROM (EPROM), electrically

EPROM (EEPROM), a flash memory, any other memory chip or
cartridge, or any other medium from which computer system **10** can
read and which is suitable for storing instructions. In the
present embodiment, an example of non-volatile media is storage

5   device **18**. Volatile media includes dynamic memory such as RAM
14.   Transmission media includes coaxial cables, copper wire or
fiber optics, including the wires that comprise bus **22**.
Transmission media can also take the form of acoustic or light
waves, such as those generated during radio wave or infrared data

10   communications.

      Moreover, the present invention may be downloaded as a
computer program product, wherein the program instructions may be
transferred from a remote computer such as a server **39** to

15   requesting computer system **10** by way of data signals embodied in
a carrier wave or other propagation medium via a network link **34**
(e.g., a modem or network connection) to a communications
interface **32** coupled to bus **22**.   Communications interface **32**
provides a two-way data communications coupling to network link

20   **34** that may be connected, for example, to a local area network
(LAN), wide area network (WAN), or as depicted herein, directly
to an Internet Service Provider (ISP) **37**.   In particular, network
link **34** may provide wired and/or wireless network communications
to one or more networks.

25

      ISP **37** in turn provides data communication services through
the Internet **38** or other network.   Internet **38** may refer to the
worldwide collection of networks and gateways that use a
particular protocol, such as Transmission Control Protocol (TCP)

30   and Internet Protocol (IP), to communicate with one another.   ISP
37 and Internet **38** both use electrical, electromagnetic, or
optical signals that carry digital or analog data streams.   The

signals through the various networks and the signals on network link **34** and through communication interface **32**, which carry the digital or analog data to and from computer system **10**, are exemplary forms of carrier waves transporting the information.

5   Further, multiple peripheral components may be added to computer system **10**. For example, an audio output **28** is attached to bus **22** for controlling audio output through a speaker or other audio projection device. A display **24** is also attached to bus **22** for providing visual, tactile or other graphical representation

10   formats. A keyboard **26** and cursor control device **30**, such as a mouse, trackball, or cursor direction keys, are coupled to bus **22** as interfaces for user inputs to computer system **10**. Keyboard **26** and cursor control device **30** can control the position of a cursor positioned within a display area of display **24**. Display **24** may

15   include both non-transparent surfaces, such as monitors, and transparent surfaces, such as headset sunglasses or vehicle windshield displays.

          It should be understood that keyboard **26** and cursor control

20   device **30** are examples of multiple types of input devices that may be utilized in the present invention. In alternate embodiments of the present invention, additional input and output peripheral components may be added.

25   RECENTLY USED TRANSLUCENCY CONTEXT

          Referring now to **Figure 2,** there is depicted a graphical representation of a user interface where audio output corresponds to the graphical characteristics of associated windows in

30   accordance with the method, system, and program of the present invention. As illustrates, a user interface **50** includes windows **52, 54,** and **56.** In the present example, window **52** is positioned

at the top level of the z-order, followed in position by window **54,** and then window **56.** As depicted, each of windows **52, 54,** and **56** are set at a particular level of transparency. In the present example, window **52** is set at 0% transparency, while window **54** is

5   set at 30% transparency and window **52** set at 50% transparency. The levels of transparency associated with windows may be reflective of multiple factors including, but not limited to, recent use, resource utilization, and other measurable factors.

10   According to one advantage of the present invention, audio associated with multiple windows may be output simultaneously, independent of whether windows are active or not. For example, audio associated with window **52** may be output simultaneously with audio associated with window **54.**

15   According to another advantage of the present invention, audio volumes may be independently selected according to the transparency of the window associated with the audio. Advantageously, a graphical indicator, such as an audio

20   specification window **58,** indicates the current windows and volume percentage associated therewith.

In the present example, the percentage of the total volume is divided in relation to the percentage of transparency of each

25   window. For example, window **52** is displayed at 0% transparency, and 60% of the total volume is displaced by audio associated with window **52.** Window **54** is displayed at 30% transparency and 30% of the total volume is displaced by audio associated with window **54.** Window 56 is displayed at 60% transparency and 10% of the total

30   volume is displaced by audio associated with window **56.**

According to a further advantage of the present invention, the dimensional position of audio output may parallel the positions of windows within user interface **50**. Particularly where multiple speaker outputs are available, the frequency and tone of sound may be adjusted to create the sound of coming from multiple points.

In the present example, window **56** is located in the top left corner of user interface **50**. Therefore the audio associated with window **56** is preferably output to sound as if it is coming from the top left corner of the sound area.

With reference now to **Figure 3**, there is illustrated a graphical representation of a user interface where windows are z-ordered according to audio utilization in accordance with the method, system, and program of the present invention. Advantageously, windows **52, 54** and **56** may be z-ordered according to CPU utilization. In the example, the transparency of the windows **52, 54,** and **56** is tied to the z-ordering criteria, and is thus selected to reflect CPU utilization by each window. Then, the audio output in association with each of windows **52, 54,** and **56** is gauged to reflect the transparency of each of windows **52, 54,** and **56**. Therefore, ultimately, audio output reflects the criteria utilized to z-order windows. As the transparency of windows adjusts according to z-ordering criteria, the audio percentage distribution preferably re-distributes.

In the present example, the criteria utilized for z-ordering windows has adjusted in comparison with the criteria utilized in **Figure 2**. The transparency of the windows has adjusted to reflect the new z-ordering criteria. In particular, the CPU utilization associated with window **56** is greater than the utilization associated with windows **52** and **54**. The transparency

of the windows is adjusted accordingly. According to the transparency of the windows, 60% of the total volume is distributed to the audio associated with window **56.**

Referring now to **Figure 4,** there is depicted a block diagram of audio preferences in accordance with the method, system, and program of the present invention. As illustrated, audio preferences **60** includes criteria for z-ordering windows, such as ordering criteria **62.** For example, CPU utilization may be set as a criteria for the z-order of windows. Preferably, a user may adjust criteria for ordering windows by selecting selectable button **66.**

In addition, audio preferences **60** may include criteria for environmental effects, such as environmental effects criteria **66.** For example, environmental effects criteria may designate audio output in association with a browser window to be whispered. In another example, environmental effects criteria may designate audio output in association with a game application to be output as if in a cave. Further, environmental effects criteria may designate audio output in associated with a window that is behind another window to be muffled in order to output the effect that the sound is behind an object.

Preferably, a user may adjust environmental effect criteria by selecting selectable button **68.** In addition, while in the present example environmental effects criteria are designated according to type of window, in alternate embodiments, environmental effects criteria may be designated according to specific applications, specific windows, groups of windows, and other criteria.

With reference now to **Figure 5**, there is illustrated a high
level logic flowchart of a process and program for adjusting
sound output according to displayable object graphical
characteristics in accordance with the method, system, and
program of the present invention. As depicted, the process
starts at block **80** and thereafter proceeds to block **81**.

Block **81** depicts a determination as to whether or not an
adjustment in sound associated with resource utilization is
detected. For example, CPU utilization by audio may be
designated as a sound associated resource utilization preference.
If an adjustment in sound associated resource utilization is not
detected, then the process passes to block **82**. If an adjustment
in sound associated resource utilization is detected, then the
process passes to block **83**. Block **83** illustrates adjusting the
transparency of each window to reflect the adjustment in resource
utilization. Next, the process passes to block **82**.

Block **82** illustrates a determination as to whether or not
there is an adjustment in current window positions or
transparency. If there are not adjustments in current window
position or transparency, then the process returns to block **81**.
If there are adjustments in current window position or
transparency, then the process passes to block **84**.

Block **84** depicts adjusting the sound percentage associated
with each window according to window positions and user
preferences. Next, block **86** illustrates applying environmental
effects to any windows meeting user environmental effect
preference criteria. Thereafter, block **88** depicts adjusting the
position of each sound to reflect the position of each associated
window; and the process ends.

While the invention has been particularly shown and described with reference to a preferred embodiment, it will be understood by those skilled in the art that various changes in form and detail may be made therein without departing from the spirit and scope of the invention.